

## CSB80 Series Wireless Doorbell

### CSB-86

MEAS.	N.W.	G.W.	OUTER
CM	kg	kg	set
61 × 49.5 × 39	14.5	15.5	80

- ◇ Operating range up to 100meters in the open area
- ◇ High frequency transmit technology and innovative "same frequency and different code" function. One wireless doorbell with one code. so it could avoid disturb with your neighborhood.
- ◇ 3 or 32 pieces of music could be optional
- ◇ Receiver uses: 3 × AA battery
- ◇ Transmitter used one 12V 23A battery
- ◇ Receiver(bell) size: 123 × 99.8 × 29.6 (mm)
- ◇ Transmitter(button) size: 78 × 39 × 21(mm)
- ◇ N.W of Receiver (bell): 124.4(g)
- ◇ N.W of Transmitter(button): 30.2(g)
- ◇ Approval: CE, RoHS, R&TTE
- ◇ Package: double blister with slide card or color box

### CSB-84

MEAS.	N.W.	G.W.	OUTER
CM	kg	kg	set
61 × 49.5 × 39	11.63	12.86	80

- ◇ Operating range up to 100meters in the open area
- ◇ High frequency transmit technology and innovative "same frequency and different code" function. One wireless doorbell with one code. so it could avoid disturb with your neighborhood.
- ◇ 3 or 32 pieces of music could be optional
- ◇ Receiver uses: 3 × AA battery
- ◇ Transmitter used one 12V 23A battery
- ◇ Receiver(bell) size: 117.8 × 78 × 28.5 (mm)
- ◇ Transmitter(button) size: 78 × 39 × 21(mm)
- ◇ N.W of Receiver (bell): 88.2(g)
- ◇ N.W of Transmitter(button): 30.2(g)
- ◇ Approval: CE, RoHS, R&TTE
- ◇ Package: double blister with slide card or color box

### CSB-83

MEAS.	N.W.	G.W.	OUTER
CM	kg	kg	set
61 × 49.5 × 39	11.63	13.13	80

- ◇ Operating range up to 100meters in the open area
- ◇ High frequency transmit technology and innovative "same frequency and different code" function. One wireless doorbell with one code. so it could avoid disturb with your neighborhood.
- ◇ 3 or 32 pieces of music could be optional
- ◇ Receiver uses: 3 × AA battery
- ◇ Transmitter used one 12V 23A battery
- ◇ Receiver(bell) size: 117.8 × 78 × 28.5 (mm)
- ◇ Transmitter(button) size: 78 × 39 × 21(mm)
- ◇ N.W of Receiver (bell): 95.8(g)
- ◇ N.W of Transmitter(button): 30.2(g)
- ◇ Approval: CE, RoHS, R&TTE
- ◇ Package: double blister with slide card or color box

### CSB-82


MEAS.	N.W.	G.W.	OUTER
CM	kg	kg	set
61 × 49.5 × 39	16.11	17.61	80

- ◇ Operating range up to 100meters in the open area
- ◇ High frequency transmit technology and innovative "same frequency and different code" function. One wireless doorbell with one code. so it could avoid disturb with your neighborhood.
- ◇ 3 or 32 pieces of music could be optional
- ◇ Receiver uses: 3 × AA battery
- ◇ Transmitter used one 12V 23A battery
- ◇ Receiver(bell) size: Φ120.3 × 38.5 (mm)
- ◇ Transmitter(button) size: 94 × 54 × 20(mm)
- ◇ N.W of Receiver (bell): 100(g)
- ◇ N.W of Transmitter(button): 51.8(g)
- ◇ Approval: CE, RoHS, R&TTE
- ◇ Package: double blister with slide card or color box

### CSB-29

MEAS.	N.W.	G.W.	OUTER
CM	kg	kg	set
61 × 49.5 × 39	16.11	17.61	80

- ◇ Operating range up to 100meters in the open area
- ◇ High frequency transmit technology and innovative "same frequency and different code" function. One wireless doorbell with one code. so it could avoid disturb with your neighborhood.
- ◇ 3 or 32 pieces of music could be optional
- ◇ Receiver uses: 2 × AAA battery
- ◇ Transmitter used one 12V 23A battery
- ◇ Receiver(bell) size: 100.5 × 55 × 32.5 (mm)
- ◇ Transmitter(button) size: 86 × 42.8 × 18.5(mm)
- ◇ N.W of Receiver (bell): 67.2(g)
- ◇ N.W of Transmitter(button): 31.2(g)
- ◇ Approval: CE, RoHS, R&TTE
- ◇ Package: double blister with slide card or color box



## CSB60 Series Wireless Doorbell

### CSB-680



MEAS.	N.W.	G.W.	OUTER
CM	kg	kg	set
61 × 49.5 × 39	14.8	15.8	80

- ◇ Self-powered button requires no batteries and other external power. Reduce waste from battery disposal.
- ◇ Operating range up to 200meters in the open area. Signal passes through walls, doors and floors
- ◇ 40 billion unique ID, never cross talk.
- ◇ Power supply of receiver: AC 110/220V.
- ◇ Power supply of transmitter: Self -powered
- ◇ Operating temperature of receiver: -10℃ to +40℃
- ◇ Operating Temperature of transmitter: -40℃ to +60℃
- ◇ 16 pieces of music could be optional
- ◇ Power Consumption of receiver: <700mW(when it rings)
- ◇ RF Frequency: 868MHz/443MHz/315MHz
- ◇ Receiver (bell): 46 × 88 × 41(mm)
- ◇ Transmitter(button) size: 68 × 86 × 46(mm)
- ◇ N W of Receiver(bell): 80(g)
- ◇ N W of Transmitter(button): 79(g)
- ◇ Approval: CE, RoHS
- ◇ Package: double blister with slide card or color box

### CSB-620



MEAS.	N.W.	G.W.	OUTER
CM	kg	kg	set
61 × 49.5 × 39	12.5	14	80

- ◇ Operating range up to 100meters in the open area. Signal Passes through walls, doors and floors.
- ◇ Power supply of receiver: AC 110/220V.
- ◇ Battery of transmitter: 12V, 23A
- ◇ Operating temperature of receiver: -10℃ to +40℃
- ◇ Operating temperature of transmitter: -40℃ to +60℃
- ◇ 32 pieces of music could optional
- ◇ Power Consumption of receiver: <700mW(when it rings)
- ◇ RF Frequency: 433MHz
- ◇ Receiver (bell): 100.5 × 55 × 32.5(mm)
- ◇ Transmitter(button) size: 86 × 42.8 × 18.5(mm)
- ◇ N W of Receiver(bell): 67.2(g)
- ◇ N W of Transmitter(button): 31.2(g)
- ◇ Approval: CE, RoHS
- ◇ Package: double blister with slide card or color box

### CSB-18



MEAS.	N.W.	G.W.	OUTER
CM	kg	kg	set
59 × 49.5 × 39	9.3	10.8	80

- ◇ Operating range up to 100meters in the open area
- ◇ High frequency transmit technology and innovative "same frequency and different code" function. One wireless doorbell with one code. so it could avoid disturb with your neighborhood.
- ◇ 3 or 32 pieces of music could be optional
- ◇ Receiver uses 2 × AA battery
- ◇ Transmitter used one 12V 23A battery
- ◇ Receiver(bell) size: 84 × 67.3 × 29.2 (mm)
- ◇ Transmitter(button) size: 85.8 × 42.7 × 18(mm)
- ◇ N.W of Receiver (bell) 56.4(g)
- ◇ N.W of Transmitter(button): 31.8(g)
- ◇ Approval: CE, RoHS, R&TTE
- ◇ Package: double blister with slide card or color box

### CSB-17



MEAS.	N.W.	G.W.	OUTER
CM	kg	kg	set
54 × 49.5 × 39	10.83	12.33	80

- ◇ Operating range up to 100meters in the open area
- ◇ High frequency transmit technology and innovative "same frequency and different code" function. One wireless doorbell with one code. so it could avoid disturb with your neighborhood.
- ◇ 3 or 32 pieces of music could be optional
- ◇ Receiver uses: 3 × AA battery
- ◇ Transmitter used one 12V 23A battery
- ◇ Receiver(bell) size: 110 × 75 × 23.8 (mm)
- ◇ Transmitter(button) size: 85.8 × 42.7 × 18(mm)
- ◇ N.W of Receiver (bell) 74.8(g)
- ◇ N.W of Transmitter(button): 31.8(g)
- ◇ Approval: CE, RoHS, R&TTE
- ◇ Package: double blister with slide card or color box



## CSB10 Series Wireless Doorbell

### CSB-16

MEAS.	N.W.	G.W.	OUTER
CM	kg	kg	set
60 × 49.5 × 39	9.9	11.4	80

- ◇ Operating range up to 100meters in the open area
- ◇ High frequency transmit technology and innovative "same frequency and different code" function. One wireless doorbell with one code. so it could avoid disturb with your neighborhood.
- ◇ 3 or 32 pieces of music could be optional
- ◇ Receiver uses: 2 × AA battery
- ◇ Transmitter used one 12V 23A battery
- ◇ Receiver(bell) size: 93.2 × 63.2 × 32.5 (mm)
- ◇ Transmitter(button) size: 85.8 × 42.7 × 18(mm)
- ◇ N.W of Receiver (bell): 57.4(g)
- ◇ N.W of Transmitter(button): 31.8(g)
- ◇ Approval: CE, RoHS, R&TTE
- ◇ Package: double blister with slide card or color box

### CSB-15

MEAS.	N.W.	G.W.	OUTER
CM	kg	kg	set
61 × 49.5 × 39	10.6	12.1	80

- ◇ Operating range up to 100meters in the open area
- ◇ High frequency transmit technology and innovative "same frequency and different code" function. One wireless doorbell with one code. so it could avoid disturb with your neighborhood.
- ◇ 3 or 32 pieces of music could be optional
- ◇ Receiver uses: 3 × AA battery
- ◇ Transmitter used one 12V 23A battery
- ◇ Receiver(bell) size: 90.5 × 61 × 33 (mm)
- ◇ Transmitter(button) size: 85.8 × 42.7 × 18(mm)
- ◇ N.W of Receiver (bell): 65.4(g)
- ◇ N.W of Transmitter(button): 31.8(g)
- ◇ Approval: CE, RoHS, R&TTE
- ◇ Package: double blister with slide card or color box

### CSB-14

MEAS.	N.W.	G.W.	OUTER
CM	kg	kg	set
57 × 49.5 × 39	9.25	10.75	80

- ◇ Operating range up to 100meters in the open area
- ◇ High frequency transmit technology and innovative "same frequency and different code" function. One wireless doorbell with one code. so it could avoid disturb with your neighborhood.
- ◇ 3 or 32 pieces of music could be optional
- ◇ Receiver uses: 2 × AAA battery
- ◇ Transmitter used one 12V 23A battery
- ◇ Receiver(bell) size: 93 × 65 × 29.5 (mm)
- ◇ Transmitter(button) size: 85.8 × 42.7 × 18(mm)
- ◇ N.W of Receiver (bell): 53.6(g)
- ◇ N.W of Transmitter(button): 31.8(g)
- ◇ Approval: CE, RoHS, R&TTE
- ◇ Package: double blister with slide card or color box

### CSB-29(1V2)

MEAS.	N.W.	G.W.	OUTER
CM	kg	kg	set
75 × 49.5 × 39	16.12	17.62	80

- ◇ Operating range up to 100meters in the open area
- ◇ High frequency transmit technology and innovative "same frequency and different code" function. One wireless doorbell with one code. so it could avoid disturb with your neighborhood.
- ◇ 3 or 32 pieces of music could be optional
- ◇ Receiver uses: 2 × AAA battery
- ◇ Transmitter used one 12V 23A battery
- ◇ Receiver(bell) size: 100.5 × 55 × 32 (mm)
- ◇ Transmitter(button) size: 86 × 42.8 × 18.5(mm)
- ◇ N.W of Receiver (bell): 67.2(g)
- ◇ N.W of Transmitter(button): 31.2(g)
- ◇ Approval: CE, RoHS, R&TTE
- ◇ Package: double blister with slide card or color box

### CSB-29(2V1)

MEAS.	N.W.	G.W.	OUTER
CM	kg	kg	set
65 × 49.5 × 39	13.12	14.62	80

- ◇ Operating range up to 100meters in the open area
- ◇ High frequency transmit technology and innovative "same frequency and different code" function. One wireless doorbell with one code. so it could avoid disturb with your neighborhood.
- ◇ 3 or 32 pieces of music could be optional
- ◇ Receiver uses: 2 × AAA battery
- ◇ Transmitter used one 12V 23A battery
- ◇ Receiver(bell) size: 100.5 × 55 × 32.5 (mm)
- ◇ Transmitter(button) size: 86 × 42.8 × 18.5(mm)
- ◇ N.W of Receiver (bell): 67.2(g)
- ◇ N.W of Transmitter(button): 31.2(g)
- ◇ Approval: CE, RoHS, R&TTE
- ◇ Package: double blister with slide card or color box



## CSB80N Series Wireless Doorbell

### CSB-84(1V2)

MEAS.	N.W.	G.W.	OUTER
CM	kg	kg	set
65 × 51.5 × 40	18.32	19.82	80

- ◇ Operating range up to 100meters in the open area
- ◇ High frequency transmit technology and innovative
- ◇ "same frequency and different code" function. One wirekess doorbell with one code .so it could avoid disturb with your neighborhood.
- ◇ 3 or 32 pieces of music could be optional
- ◇ Receiver uses:3 × AA battery
- ◇ Transmitter used one 12V 23A battery
- ◇ Receiver(bell)size:117.8 × 78 × 28.5 (mm)
- ◇ Transmitter(button)size:78 × 39 × 21(mm)
- ◇ N.W of Receiver (bell)88.2(g)
- ◇ N.W of Transmitter(button):30.2(g)
- ◇ Approval:CE,RoHS,R&TTE
- ◇ Package:double blister with slide card or color box

### CSB-84(2V1)

MEAS.	N.W.	G.W.	OUTER
CM	kg	kg	set
61 × 43.5 × 40	13.65	15.51	80

- ◇ Operating range up to 100meters in the open area
- ◇ High frequency transmit technology and innovative
- ◇ "same frequency and different code" function. One wirekess doorbell with one code .so it could avoid disturb with your neighborhood.
- ◇ 3 or 32 pieces of music could be optional
- ◇ Receiver uses:3 × AA battery
- ◇ Transmitter used one 12V 23A battery
- ◇ Receiver(bell)size:117.8 × 78 × 28.5 (mm)
- ◇ Transmitter(button)size:78 × 39 × 21(mm)
- ◇ N.W of Receiver (bell)88.2(g)
- ◇ N.W of Transmitter(button):30.2(g)
- ◇ Approval:CE,RoHS,R&TTE
- ◇ Package:double blister with slide card or color box

### CSB-83(1V2)

MEAS.	N.W.	G.W.	OUTER
CM	kg	kg	set
65 × 51.5 × 40	18.7	20.2	80

- ◇ Operating range up to 100meters in the open area
- ◇ High frequency transmit technology and innovative
- ◇ "same frequency and different code" function. One wirekess doorbell with one code. so it could avoid disturb with your neighborhood.
- ◇ 3 or 32 pieces of music could be optional
- ◇ Receiver uses:3 × AA battery
- ◇ Transmitter used one 12V 23A battery
- ◇ Receiver(bell)size:117.8 × 78 × 28.5 (mm)
- ◇ Transmitter(button)size:78 × 39 × 21(mm)
- ◇ N.W of Receiver (bell)95.8(g)
- ◇ N.W of Transmitter(button):30.2(g)
- ◇ Approval:CE,RoHS,R&TTE
- ◇ Package:double blister with slide card or color box

### CSB-83(2V1)

MEAS.	N.W.	G.W.	OUTER
CM	kg	kg	set
61 × 43.5 × 40	13.82	14.78	80

- ◇ Operating range up to 100meters in the open area
- ◇ High frequency transmit technology and innovative
- ◇ "same frequency and different code" function. One wirekess doorbell with one code. so it could avoid disturb with your neighborhood.
- ◇ 3 or 32 pieces of music could be optional
- ◇ Receiver uses:3 × AA battery
- ◇ Transmitter used one 12V 23A battery
- ◇ Receiver(bell)size:117.8 × 78 × 28.5 (mm)
- ◇ Transmitter(button)size:78 × 39 × 21(mm)
- ◇ N.W of Receiver (bell)95.8(g)
- ◇ N.W of Transmitter(button):30.2(g)
- ◇ Approval:CE,RoHS,R&TTE
- ◇ Package:double blister with slide card or color box

## CSC-S Series Remote Control Socket

### CSC-S316A(1000W)

MEAS.	N.W.	G.W.	OUTER
CM	kg	kg	set
64 × 34.5 × 49.5	7.2	8.7	40

- ◇ No installation is need.ready for instant operation.
- ◇ Range up to approx:50m.
- ◇ Individual adjustments can be made for system and receiver codifications to avokd crossovers with similar equipments in you neighborhood.
- ◇ Power:1000W.Voltage:230VAC.Frequency:50/60Hz
- ◇ Battry(1 × 12V,type 23A)for the radio remote control is included.
- ◇ Transmitter frequency:433.92MHz,315MHz
- ◇ Waterproof cover:IP20
- ◇ Approval:CE,TUV GS.
- ◇ Receiver(socket) size:95.7 × 51.7 × 69(mm)
- ◇ Transmitter (button) size:94.7 × 39.7 × 18(mm)
- ◇ N.W of receiver:108(g)
- ◇ N.W of transmitter:51(g)
- ◇ Package:blister card

### CSC-S316A(3600W)

MEAS.	N.W.	G.W.	OUTER
CM	kg	kg	set
57.5 × 34.5 × 49.5	8.5	10	40

- ◇ No installation is need.ready for instant operation.
- ◇ Range up to approx:50m.
- ◇ Individual adjustments can be made for system and receiver codifications to avokd crossovers with similar equipments in you neighborhood.
- ◇ Power:3600W.Voltage:230VAC.Frequency:50/60Hz
- ◇ Battry(1 × 12V,type 23A)for the radio remote control is included.
- ◇ Transmitter frequency:433.92MHz,315MHz
- ◇ Waterproof cover:IP20
- ◇ Approval:CE,TUV GS.
- ◇ Receiver(socket) size:103.5 × 60.6 × 79.8(mm)
- ◇ Transmitter (button) size:94.7 × 39.7 × 18(mm)
- ◇ N.W of receiver:146(g)
- ◇ N.W of transmitter:51(g)
- ◇ Package:blister card

### CSC-S316IA(1000W)

MEAS.	N.W.	G.W.	OUTER
CM	kg	kg	set
74.5 × 34.5 × 49.5	9.33	10.83	40

- ◇ No installation is need.ready for instant operation.
- ◇ Range up to approx:50m.
- ◇ Individual adjustments can be made for system and receiver codifications to avokd crossovers with similar equipments in you neighborhood.
- ◇ Power:1000W.Voltage:230VAC.Frequency:50/60Hz
- ◇ Battry(1 × 12V,type 23A)for the radio remote control is included.
- ◇ Transmitter frequency:433.92MHz,315MHz
- ◇ Waterproof cover:IP44
- ◇ Approval:CE,TUV GS.
- ◇ Receiver(socket) size:104.8 × 60.6 × 90.1(mm)
- ◇ Transmitter (button) size:94.7 × 39.7 × 18(mm)
- ◇ N.W of receiver:160.8(g)
- ◇ N.W of transmitter:51(g)
- ◇ Package:blister card

### CSC-S316IA(3600W)

MEAS.	N.W.	G.W.	OUTER
CM	kg	kg	set
74.5 × 34.5 × 49.5	9.45	10.95	40

- ◇ No installation is need.ready for instant operation.
- ◇ Range up to approx:50m.
- ◇ Individual adjustments can be made for system and receiver codifications to avokd crossovers with similar equipments in you neighborhood.
- ◇ Power:3600W.Voltage:230VAC.Frequency:50/60Hz
- ◇ Battry(1 × 12V,type 23A)for the radio remote control is included.
- ◇ Transmitter frequency:433.92MHz,315MHz
- ◇ Waterproof cover:IP44
- ◇ Approval:CE,TUV GS.
- ◇ Receiver(socket) size:104.8 × 60.6 × 90.1(mm)
- ◇ Transmitter (button) size:94.7 × 39.7 × 18(mm)
- ◇ N.W of receiver:160.8(g)
- ◇ N.W of transmitter:51(g)
- ◇ Package:blister card





## CSC-S Series Remote Control Socket

### CSC-S316A(1V3)

MEAS. CM	N.W. kg	G.W. kg	OUTER set
64.5 × 54.9 × 54.9	15.92	17.42	40



- ◇ No installation is need.ready for instant operation.
- ◇ Range up to approx:50m.
- ◇ Individual adjustments can be made for system and receiver codifications to avokd crossovers with similar equipments in you neighborhood.
- ◇ Power : 1000W/3600W.Voltage:230VAC.
- ◇ Frequency:50/60Hz
- Battry(1 × 12V,type 23A)for the radio remote control is included.
- ◇ Transmitter frequency:433.92MHz,315MHz
- ◇ Waterproof cover:IP20
- ◇ Approval:CE,TUV GS.
- ◇ Receiver(socket) size:5.7 × 51.7 × 69(mm)
- ◇ Transmitter (button) size:94.7 × 39.7 × 18(mm)
- ◇ N.W of receiver:108(g)
- ◇ N.W of transmitter:51(g)
- ◇ Package:blister card

### CSC-S316A(1V3)

MEAS. CM	N.W. kg	G.W. kg	OUTER set
74.5 × 60.1 × 58.5	22.57	24.07	40



- ◇ No installation is need.ready for instant operation.
- ◇ Range up to approx:50m.
- ◇ Individual adjustments can be made for system and receiver codifications to avokd crossovers with similar equipments in you neighborhood.
- ◇ Power : 1000W/3600W.Voltage:230VAC.
- ◇ Frequency:50/60Hz
- Battry(1 × 12V,type 23A)for the radio remote control is included.
- ◇ Transmitter frequency:433.92MHz,315MHz
- ◇ Waterproof cover:IP44
- ◇ Approval:CE,TUV GS.
- ◇ Receiver(socket) size:104.8 × 60.6 × 90.1(mm)
- ◇ Transmitter (button) size:94.7 × 39.7 × 18(mm)
- ◇ N.W of receiver:160.8(g)
- ◇ N.W of transmitter:51(g)
- ◇ Package:blister card